

Kiesel Bauchemie Tile and Stone installation systems product recommendation for Nuheat in North America

Setting materials for:



- 1. Servoflex-Trio-SuperTec
- 2. Servoflex-Trio-SuperTec schnell
- 3. Servolight S2 SuperTec

Primer/bonding agent:

1. Okatmos[®] UG 30 [®] *

Self-levelling compounds:

- 1. Servoplan P200 Plus *
- 2. Servoplan S 444 *

Technical Support & Marketing North America Technical Department of North America

Toll-Free: 1.888.KIESEL1 (5437351) General inquires:

info.canada@kiesel.com mailto:info.usa@kiesel.com Grout:

- 1. Servoperl royal
- 2. Servoperl royal schnell
- 3. Okapox royal
- 4. Oka Color Magic
- 5. Servofix HBF SuperTec

Silicones:

- 1. Oka Silicone
- 2. Oka Silicone M

Germany Head Office: Kiesel Bauchemie GmbH u.Co. KG Wolf-Hirth-Str. 2 D-73730 Esslingen Germany kiesel@kiesel.com

*Underneath Nuheat Membrane by Progress Profiles as a part of Kiesel floor preparation system prior to Nuheat Membrane by Progress Profiles membrane installation. Above mentioned Nuheat product must be adhered with specified Kiesel products. Kiesel products must be mixed and applied as per our strict instructions in the respective technical data sheets.

In case of doubt contact Kiesel Technical Department of North America.

The aforementioned information, especially the suggestions for processing and utilizing our product, is based on our knowledge and experience. We recommend that you carry out your own tests in every case to ensure the suitability of our products for the intended process and processing purposes as different materials and the working conditions which lie beyond our area of influence. No liability can be derived from this advice or from verbal advice, unless we are responsible for (criminal) intent or gross negligence in this respect.

Please contact Kiesel technical department before commencing commercial jobs for additional guidelines. Kiesel Bauchemie does not recommend to install tiles over freshly installed Nuheat Membrane by Progress Profiles. This recommendation refers to interior dry areas installations only (contact Kiesel technical department for further guidelines regarding exterior installations).