CABLE



FLOOR HEATING SYSTEM



FAST FACTS:

- · Heats tile, stone and laminate/engineered wood floors
- Suitable for wet environments such as showers and steam rooms
- Larger kits available (up to 120 sq ft in 120V and 240 sq ft in 240V)
- · Redesigned, thinner cold-lead and factory splice
- · New mid-point marker on heating cable
- · Completely redesigned, easy-to-use cable guide
- · Zero EMF (electromagnetic field) cable design
- · Industry-leading customer service
- · 25-year warranty

APPLICATIONS:

nVent NUHEAT Cable is an ideal room specific heat source option for kitchens, bathrooms and other spaces where on-site adjustments are required.

HOW TO ORDER & PURCHASE NUHEAT CABLE:

- Calculate the square footage of the heated area(measuring instructions available at nVent.com/NUHEAT/floor-heating/electric-floor-heat/cable.html
- 2. Determine the proper cable kit for your project
- 3. Fax a purchase order to Nuheat at 1.604.529.4404
- 4. If unsure which floor heating solution is best, contact the Nuheat Customer Care Team and a representative will recommend the appropriate cable kits and controls for your project

Wuheat-SB-H59299-CableSellSheet-EN-1805 nVent.com | 1

^{*} You can also complete a quote request via our online quote request tool available at http://nVent.com/NUHEAT/contact-us/customer-quote/

NUHEAT CABLE SPECS:

- Available in 120V and 240V
- · Thinner cold-lead and factory splice
- · Energy efficient
- (12 watts/sq ft; 41 BTUs/sq ft)

NUHEAT CABLE ELECTRICAL DETAILS:

- Largest 120V kit covers 120 square feet and largest 240V kit covers 240 square feet, producing 41 BTUs per square foot
- Nuheat controls are equipped with ground fault circuit protection (G.F.C.I.)
- · All Nuheat thermostats come with a floor sensing probe
- Electrical installation instructions are available at nVent.com/NUHEAT

INSTALLING THE NUHEAT CABLE











Install Nuheat Cable Apply Aelf-Leveler

A certified electrician connects the system to your household wiring.

A professional tile setter installs Nuheat Mat onto the subfloor.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com



Our powerful portfolio of brands:

CADDY

nVent.com