

Nuheat Cable with Nuheat Membrane

THE INTEGRATED ELECTRIC FLOOR HEATING AND UNCOUPLING SOLUTION

Nuheat Membrane and Nuheat Cable form a best in class uncoupling and heated floors solution preventing tile cracks as a result of stress caused by movement between floor layers.

The combined products provide a waterproof solution, as well as floor movement protection. The system also simplifies the installers' lives, as there is no need for metal or plastic guides and self-leveler.

Suitable floor surfaces for installing Nuheat Membrane includes tile and stone. See our recommended list of materials you will need and some instructions on how to install Nuheat Membrane for such surfaces.

TILE/STONE APPLICATIONS

LIST OF MATERIALS NEEDED:

1. Thinset
2. Flat trowel
3. ¼ inch x 3/8" square or u-notched trowel
4. Grouting float or roller
5. Thinset mixer
6. Bucket

Nuheat Membrane is a tile underlayment that accepts the Nuheat Cable Floor Heating System. Simply roll out and secure the Nuheat Membrane onto the subfloor, secure Nuheat Cable into the membrane, and proceed with the tile installation.

WATERPROOF APPLICATIONS

If your installation requires waterproofing the subfloor, simply install Proband 150 tape to cover the seams (applicable if adjacent sheets/seams are present) and the corners along the perimeter of the floor area.

LEVEL OF DIFFICULTY: Moderate

ESTIMATED TIME: 75 minutes
(based on 50 square feet)